

ZOOMLION

CRAWLER SCISSOR LIFT (OUTDOOR)

ZS2242CO

Comply with CE Standard

HIGHLIGHTS

High Performance

- ▶ Work height of 8.8m with high working efficiency
- ▶ Rubber crawler provides small ground pressure and great obstacle crossing ability
- ▶ Pivot steering with good maneuverability
- ▶ Simple single handle control for steering and walking

Cost Effectiveness

- ▶ Knuckles lubrication-free and maintenance-free
- ▶ AC motor full lifecycle maintenance-free

FEATURES

Standard Features

BMS (Battery Management System)	On-board diagnostic
Proportional controls	Over tilt protective system
All motion alarm	Active pothole protection system
Fold-down handrails	Horn
Flashing beacon	Hour meter
Self-closing entry gate	Extension deck (unidirectional)
Load sensing system	Charging protection system
Autobrake system	Scissor maintenance prop
Emergency descent system	Forklift pockets
Emergency stop button	AC power to platform

Accessories & Options

- ▶ Platform work lights
- ▶ Airline to platform
- ▶ Overhead protection bar



ACCESS WITH ZOOMLION GREEN

Phone: 1 (833) USA-ZOOM
E-mail: sales@zoomlion-na.com

Add: Zoomlion Heavy Industry (NA), Inc. 14215 Two Mile Road, Yorkville, WI 53126
Web: www.zoomlion-na.com

SKYTECH
ELEVATION 

2540, Route 122
St-Cyrille-de-Wendover, QC, J1Z 1C1
Tél.: 819-472-2225
www.skytechelevation.com

CRAWLER SCISSOR LIFT (OUTDOOR)

ZS2242CO

Comply with CE Standard

Model	ZS2242CO	
	Imperial	Metric
Size		
Work Height (Indoor/Outdoor)	28ft 11in/26ft 3in	8.80m/8m
A Platform Height-Elevated (Indoor/Outdoor)	22ft 4in/19ft 8in	6.80m/6m
B Platform Height-Stowed	3ft 8in	1.12m
C Platform Length	6ft 4in	1.94m
D Platform Width	3ft 1in	0.95m
Platform Extension	3ft	0.91m
E Overall Height (Rails Up)	7ft 5in	2.26m
Overall Height (Rails Down)	5ft 10in	1.77m
F Overall Length	6ft 11in	2.1m
G Overall Width	3ft 5in	1.05m
H Ground Clearance	5in	0.127m
Performance		
Platform Capacity	550lb	250kg
Capacity on Deck Extension	250lb	113kg
Max. Number of Workers (Indoor/Outdoor)	2/1	
Drive Speed (Stowed)	1.25mph	2km/h
Drive Speed (Raised)	0mph	0km/h
Turning Radius	0in	0m
Drive Motor	24V/2×1.8KW	
Up/Down Time	34s/30s	
Gradeability	30%(17°)	
Max. Working Slope (Lateral/Vertical)	2°/2°	
Drive	Rear Wheels	
Brake	Rear Wheels	
Power		
Battery	4×6V/220Ah (HOPPECKE) 4×12V/270Ah (QUIMO)	
Charger	24V/30	
Weight		
Gross	3750lb	1700kg

